

**CLAIM AMENDMENTS**

This listing of the claims will replace all prior versions, and listings, of claims in the application.

1. (Currently amended) A method of identifying a device, the method comprising:  
receiving a request to establish a Point to Point Protocol over Ethernet (PPPoE) session  
on behalf of a Local Area Network (LAN) side device that is a LAN node in a  
LAN that is in communication with a router;  
outputting a PPPoE discovery stage packet that comprises a tag identifying the LAN side  
device;  
receiving a different request to establish a different PPPoE session on behalf of a  
different LAN side device, the different LAN side device at a different LAN node  
of the LAN;  
outputting a different PPPoE discovery stage packet that comprises a different tag  
identifying the different LAN side device;  
receiving an access concentrator packet responsive to the PPPoE discovery stage packet,  
the access concentrator packet including the tag;  
recognizing the tag in the access concentrator packet;  
communicating the tag from the access concentrator packet to the LAN side device;  
enabling a Point to Point Protocol (PPP) session for the LAN side device, the LAN side  
device that is identified as the requesting device of the PPP session; and  
enabling a different Point to Point Protocol (PPP) session for the different LAN side  
device, the different LAN side device that is identified as the requesting device of  
the different PPP session.
2. (Original) The method of claim 1, wherein the PPPoE discovery stage packet  
comprises a PPPoE Active Discovery Initiation packet.
3. (Original) The method of claim 1, further comprising maintaining information  
associating the LAN side device with the tag and the different LAN side device with the different  
tag.

4-5. (Canceled).

6. (Previously presented) The method of claim 1, wherein the access concentrator packet comprises a PPPoE Active Discovery Offer packet and comprises the tag in an unmodified form.

7. (Original) The method of claim 1, wherein the tag complies with a Host-Uniq TAG construct described in IETF RFC 2516.

8. (Original) The method of claim 1, further comprising utilizing a PPPoE client executing at a node at least partially interconnecting a LAN to a wide area network node to generate the PPPoE discovery stage packet.

9. (Canceled).

10. (Previously presented) The method of claim 1, further comprising disabling a Network Address Translation feature in connection with the PPP session.

11. (Original) The method of claim 1, further comprising receiving the request via a connection type selected from the group consisting of an Ethernet Link, an 802.11(x) link, a Bluetooth link, a Universal Serial Bus Link, and a powerline networking link.

12. (Original) The method of claim 1, further comprising utilizing a modem device to output the PPPoE discovery stage packet, wherein the modem device is selected from the group consisting of an xDSL modem, a cable modem, a fixed wireless modem and a satellite modem.

13. (Previously presented) The method of claim 12, further comprising:  
utilizing the modem device to output the PPPoE discovery stage packet and the different PPPoE discovery stage packet; and  
communicatively coupling the modem device and a plurality of other modem devices to an access concentrator node of a wide area network.

14. (Currently amended) A device identification system, comprising:

- an access concentrator having a computing platform and an interface operable to facilitate a communicative coupling of a plurality of remote devices to the computing platform, wherein the access concentrator includes one of:
  - a cable modem termination system; and
  - a digital subscriber line access multiplexer;
- a second interface communicatively coupled to the computing platform and operable to facilitate an outputting of a collection of information representing a PPP session of a first of the plurality of remote devices and a different PPP session of a different one of the plurality of remote devices; and
- a Local Area Network (LAN) engine communicatively coupled to the interface and configured to recognize an identification tag in a packet included in a discovery stage of the PPP session, the identification tag identifying a subscriber LAN device communicating the packet via the first of the plurality of remote devices, wherein the subscriber LAN device is a LAN side device that is a LAN node in a LAN that is in communication with a router and is identified as the requesting device of the PPP session, and wherein the LAN engine is configured to recognize a different identification tag in a different packet included in a discovery stage of the different PPP session that identifies a different subscriber LAN device communicating the different packet via a different one of the plurality of remote devices and is a LAN side device that is a different LAN node in the LAN and is identified as the requesting device of the different PPP session; and

wherein the LAN engine is at least partially embodied by a processor accessing a computer-readable medium having computer-readable instructions and executing the computer-readable instructions to recognize an existence of the tag, to identify device identification information contained in the tag, and to update a memory associated with a Broadband Remote Access Server to acknowledge the device identification information.

15. (Original) The system of claim 14, wherein the tag complies with a Host-Uniq TAG construct described in IETF RFC 2516.

16. (Canceled).

17. (Original) The system of claim 14, further comprising the first of the plurality of remote devices, wherein the first of the plurality of remote devices comprises an xDSL modem.

18-19.(Canceled).

20. (Previously presented) The system of claim 14, wherein the Broadband Remote Access Server is communicatively coupled to the LAN engine and operable to maintain information representing the subscriber LAN device.

21. (Currently amended) A method of identifying remote devices, comprising:  
receiving a PPPoE packet from a remote node;  
recognizing that the PPPoE packet comprises a tag including information associated with  
a device communicating via the remote node, wherein the device and a different  
device are distinct LAN nodes in a LAN and are in communication with a router,  
wherein the device is identified as communicating via the remote node and  
requesting a Point to Point Protocol (PPP) session, wherein the device is selected  
from a group consisting of:  
a computer;  
a wireless access point;  
a Universal Serial Bus Device;  
a Voice over Internet Protocol Telephone;  
a television;  
a set-top box;  
a refrigerator;  
a washing machine; and  
a home networking device;  
receiving another PPPoE packet from the remote node;  
recognizing that the other PPPoE packet comprises a different tag including other  
information associated with a the different device communicating via the remote  
node, wherein the different device is identified as communicating via the remote  
node and requesting a different PPP session; and  
providing a broadband link at least partially interconnecting a communication network  
node and the remote node.

22. (Original) The method of claim 21, further comprising:  
associating the remote node with a subscriber; and  
maintaining subscriber information comprising an identification of the device and the  
different device.

23. (Canceled).

24. (Original) The method of claim 21, wherein the PPPoE packet comprises a PPPoE Active Discovery Initiation (PADI) packet.

25. (Previously presented) The method of claim 22, further comprising:  
altering a cost of using the broadband link in response to recognizing an additional device  
communicating with the communication network node via the remote node.

26. (Previously presented) The method of claim 22, further comprising:  
considering the subscriber information in connection with generating a marketing offer  
presentable to the subscriber.

27. (Previously presented) The method of claim 22, further comprising:  
considering the subscriber information in connection with making a communication  
network planning decision.

28. (Previously presented) The method of claim 22, further comprising:  
receiving a trouble-shooting request from the subscriber; and  
considering the subscriber information in connection with offering a suggestion  
responsive to the trouble-shooting request.

29. (Original) The method of claim 21, wherein the communication network node  
comprises a Broadband Remote Access Server.

30. (Canceled).

31. (Original) The method of claim 21, wherein the tag comprises a sixteen bit tag

32. (Original) The method of claim 21, wherein the tag comprises with a Host-Uniq TAG  
construct described in IETF RFC 2516.